



DROP DECK TRAILER

Frame

- 24 3/4" Deep Fabricated Steel Beam
 - 130k p.s.i. Minimum Yield Flanges
 - 3/8" x 5" Top Deck, 3/8" x 5" Lower Deck
 - 3/16" 80k p.s.i. Minimum Yield Web
- 6" Structural Side Rail
- Crossmembers - 14" Centers, 4" I. i Beams, 3/8" x 2 1/2" Rub Rail
- 1 1/4" Pipe Spoils Between Stake Pockets
- 24" Kingpin Setting
- 48" 5th Wheel Height
- High Strength Fabricated Knee Braces

Undercarriage

AIR RIDE OR SPRING SUSPENSION

- 5" Round Axles - 25,000 # Capacity
- 30/30 Spring Brakes
- 16.5" x 7" Cam Operated "Q" Type Shoes
 - Automatic Slacks, Outboard Drums
- Steel Disc Wheels
- Radials

Landing Gear

- 2 Speed 50,000 Lbs.

Electrical

- Grote Sealed Light System - 7 yr. warranty
- 3 Tail Lights Each Side
- Mid-Turn Signal Both Sides
- Front and Rear Marker Lights
- All lights LED
- 7-Way Socket
- Wabco Anti-Lock Brake System

Finish

- All Metal Surfaces - Cleaned, Phosphatized and Painted with a 2-Part Urethane
- Standard Color - Black (Other Colors Upon Request)
- Mud Flaps
- DOT Standard Reflective Tape
- Heavy Duty Dock Bumpers (*only on Drop Deck Trailer*)

Flooring

- 1 1/8" "One Piece" Apitong Attached with 5/16" Floor Screws

Options

- Ask About Our Many "Non-Standard" Models As Well As Optional Equipment

*** Modifications for Beaver Tail Trailer**

Frame

- 25" Deep Fabricated Steel Beam
- 3/8" x 5" Top Deck, 1/2" x 5" Lower Deck

Electrical

- 2 Tail Lights Each Side

Beavertail

- 5' Length with 18° Slope - with 2 Spring Assist Fold-Up Ramps